



LCD MONITOR

Display size	22" (55,88 cm) WIDE			
Panel Type	Active Matrix TFT			
Brightness	300 cd/m <sup>2</sup> (typ.)			
Contrast (typ.)	1000:1			
X-Contrast (dyn.)	-			
Pixel pitch	0,282(H) x 0,282(V) mm			
Resolution (H x V)	WSXGA+ 1680 x 1050			
Response time	5 ms (typ.)			
View angles (CR>10)	H/V 170° / 160°			
View angles (CR>5)				
Display colors	16,7 Mio colors			
Display Surface	AG			
Input 1	VGA, Audio			
Input 2	DVI (HDCP)			
Input 3				
Headphone				
Speakers	1,5 W x 2			
Supply	AC 100~240V, 50~60Hz			
Consumption	<b>On:</b>	40 W	<b>Stand-by:</b>	< 2 W
			<b>Off:</b>	< 1 W
Operation Temp/Hum	5 ~ 40°C		20 ~ 80%	
Dimension (W*D*H)	510 x 202 x 424 mm			
Net weight	4,9 kg			
Tilt	0°~ 20°			
Kensington Lock	✓			
VESA mounting	VESA Standard, 100mm			
On screen display	EN, GE, FR, IT, SP, JP, CN, RU, NO, NL, PL, PT, SW,			
Safety	CE, FCC, BSMI, C-Tick, VCCI, CB, UL/CUL, MIC, BAU-MARK, CCC, GOST			
Emission	TCO03			
Power saving	EnergyStar			
Extras 1	Windows VISTA Premium			
Extras 2				
Extras 3				
EAN	4710859555267			
incl Accessory	1.8m Power Cord, 1.8m VGA cable, Audio Cable, CD Menu & QSG			



© HANNspree Europe GmbH. Information in this document is subject to change without notice. All brand-, product-, service names and logos are trademarks and/or registered trademarks of their respective manufacturers and companies. Screenshots are simulated.